TECHNICAL FACT SHEET



Series 140-9107/00

Scratch-off White for Flexo Printing

Series 140-9107/33 is a scratch-off white for flexo printing. The series is part of a unique UV flexo printing range for the printing of scratch-off layers.

Roll type	Anilox roll Pick-up volume 12–22 cm³/m², lining 70-100 lines/cm
Printing speed	15-25 m/min
Curing	80-200 mJ/cm ² (Technigraf Integrator)
Substrates	Paper, cardboard, rigid PVC, soft PVC, OPP (preliminary test required), offset varnished
Further processing	Punching, cutting
Available quantities	1 kg, 5 kg, 20 kg
Shelf life	See information on the container lid.
Others	Stir well before use. Protect from light.

Specifications

Important information: Our technical advice, whether spoken, written, or through test trials corresponds to our current knowledge to inform about our products and their use. This is not meant as an assurance for certain properties of the products nor their suitability for each application. You are, therefore, obliged to conduct your own tests with our supplied products to confirm their suitability for the desired process or purpose. The selection and testing of the ink for specific applications is exclusively your responsibility. Should, however, any liability claims arise, such claims shall be limited to the value of the goods delivered by us and utilized by you with respect to any and all damages not caused intentionally or by gross negligence. (T30 / 05/2021)