

# Series 2550-L-HG/002

## UV Spray Varnish, high gloss

The high gloss UV spray varnish Series 2550-L-HG/002 was developed for the mechanical protection of plastic parts. Especially for ABS with and without preprint. Ideally, and depending on the substrate, the coating is sprayed on with a layer thickness of 25 to 40 µm.

### Specifications

<b>Thinner</b>	-
<b>Addition ratio</b>	-
<b>Retarder</b>	-
<b>Addition ratio</b>	-
<b>Hardener</b>	-
<b>Addition ratio</b>	-
<b>Cleaner</b>	Series 500-URS
<b>Nozzle</b>	0.7 mm (pre-tests recommended)
<b>Curing</b>	Min. 800 mJ/cm <sup>2</sup> (Technigraf Integrator)
<b>Substrates</b>	ABS
<b>Indoor use / outdoor use</b>	Indoor
<b>Further processing</b>	-
<b>Overprintability</b>	-
<b>Delivery conditions</b>	1 kg, 5 kg, 20 kg
<b>Shelf life</b>	12 months
<b>Others</b>	Recommended processing temperature approx. 40 °C

**Important information:** Our technical advice whether spoken, written, or through test trials corresponds to our current knowledge to inform about our products and their use. This is not meant as an assurance for certain properties of the products nor for their suitability for each application. You are, therefore, obliged to conduct your own tests with our supplied products to confirm their suitability for the desired process or purpose. The selection and testing of the ink for specific applications is exclusively your responsibility. Should, however, any liability claims arise, such claims shall be limited to the value of the goods delivered by us and utilized by you with respect to any and all damages not caused intentionally or by gross negligence. (T28/T12 / V1 / 11/2022)