

Series 471-002

Magic Wipe, damp wipeable varnish

Magic Wipe is a removable special varnish for the full or partial finishing of offset prints. Magic Wipe can be wiped off using a damp cloth, not leaving any residue. The varnish can be colored with pigment pastes Series 420-PMxx or other effect pigments.

Pigment pastes for coloring (addition ratio 10–30 %)

420-PM10	Pigment paste yellow MS-1000	420-PM33	Pigment paste magenta MS-3300
420-PM11	Pigment paste yellow MS-1100	420-PM40	Pigment paste violet MS-4000
420-PM12	Pigment paste yellow MS-1200	420-PM50	Pigment paste blue MS-5000
420-PM20	Pigment paste orange MS-2000	420-PM60	Pigment paste green MS-6000
420-PM30	Pigment paste red MS-3000	420-PM80	Pigment paste black MS-8000
420-PM31	Pigment paste red MS-3100	420-PM90	Pigment paste white MS-9000
420-PM32	Pigment paste dark red MS-3200		

Application example

A manufacturer prints a glossy sales brochure for his new off-road vehicles (offset print with UV varnished front page). Matching the image, the vehicle has to look dirty, attracting the attention of potential clients. This is where Series 471-002 colored with pigment pastes is used to visualize mud and dirt. When the client is holding the brochure in his hands later on, Magic Wipe can be wiped off using a damp cloth – revealing the sparkling clean SUV underneath.

Specifications

Thinner	Press-ready (water if necessary)
Addition ratio	Max. 10 % if necessary
Wetting agent	Series 400-BMS
Addition ratio	1–3 % by weight
Mesh	120.34 to 77.55
Drying	Air / jet up to 80 °C
Substrates	Coatings and laminates
Application	Offset finishing
Further processing	-
Delivery conditions	1 kg, 5 kg, 20 kg Pigment pastes are also available in containers of 200 g.
Shelf life	12 months
Others	Stir well before use. Store at 10–30 °C, protect from frost. Care has to be taken that only water resistant meshes are being used.

Important Information: Our technical advice whether spoken, written, or through test trials corresponds to our current knowledge to inform about our products and their use. This is not meant as an assurance for certain properties of the products nor for their suitability for each application. You are, therefore, obliged to conduct your own tests with our supplied products to confirm their suitability for the desired process or purpose. The selection and testing of the ink for specific applications is exclusively your responsibility. Should, however, any liability claims arise, such claims shall be limited to the value of the goods delivered by us and utilized by you with respect to any and all damages not caused intentionally or by gross negligence. This technical datasheet supersedes all previous datasheets, which thereby become invalid. (T12/T26 / V1 / 10/2016)